MEC J-14258

## **ELEVATION CERTIFICATE**

## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No. 3067-0077 Expires July 31, 1999

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages. SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE BUILDING OWNER'S NAME POLICY NUMBER J.C. HIND, Jr. STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER 1640 VALENCIA DR. OTHER DESCRIPTION (Lot and Block Numbers, etc.) WTS 11 \$ 12 BLOCK 23, FLORARY MERRY ACRES S/O STATE ZIP CODE CITY 31707 SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 6. BASE FLOOD ELEVATION (in AO Zones, use depth) 3. SUFFIX 4. DATE OF FIRM INDEX 5. FIRM ZONE 1. COMMUNITY NUMBER 2. PANEL NUMBER MARCH 18, 1985 C /3*00*75 0015 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate SECTION C BUILDING ELEVATION INFORMATION 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level 8. 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation (b), FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of Lillibli leet NGVD (or other FIRM datum-see Section B. Item 7). below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is . . . feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 🗌 Yes 🔲 No 🔲 Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Yes No (See Instructions on Page 4) 5. The reference level elevation is based on: X actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: \( \begin{align\*} | \begin{ali Section B, Item 7). SECTION D COMMUNITY INFORMATION 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1

2. Date of the start of construction or substantial improvement

floor" as defined by the ordinance is: LLLLLL. feet NGVD (or other FIRM datum-see Section B. Item 7).

is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest


## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE), V1–V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal)			
Ritchey M. Marbury, III		GA R.L.S. 1495		
TITLE	COMPANY NAM			
President	Marbury Engineering Co.			
ADDRESS	CITY		STATE	ZIP
2334 Lake Park Drive	Albany ,		GA	31707
SIGNATURE Within M. Marfrey, Tet	DATE PHONE 912-435-6133		6133	
COMMENTS: SECTION B ITEX	18 - CON	IMUNITY'S BFE	As	•
COMMENTS: <u>SECTION</u> B ITEA ESTABLISHED BY CITY OF				



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.